

Water Dispenser Catalog



desktop water dispenser

MOQ : 50-100



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs	9kgs/10kgs
Packaging Dimension	310*310*420mm	310*310*420mm	330*340*540mm
Loading Qty	686pcs/20'FT	686pcs/20'FT	476pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃



Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs



Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot , Warm and C	Hot , Warm and C
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm



Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot 、 Warm and Cold	Hot 、 Warm and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot 、 Warm and Cold	Hot 、 Warm and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot 、 Warm and Cold	Hot 、 Warm and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V/240V,50/60Hz	220V/240V,50/60Hz	220V/240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V/240V,50/60Hz	220V/240V,50/60Hz	220V/240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V/240V,50/60Hz	220V/240V,50/60Hz	220V/240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ

FOB Ningbo			
------------	--	--	--



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V/240V,50/60Hz	220V/240V,50/60Hz	220V/240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot and Cold	Hot and Cold
Cooling Method	/	Electric Cooling	Compressor Cooling
Rated Voltage/Frequency	220V/240V,50/60Hz	220V/240V,50/60Hz	220V/240V,50/60Hz
Heating power	550w	550w	550w
Cooling power	/	75W	80W
Hot temperature	85-95℃	85-95℃	85-95℃
Cold temperature	/	10-15℃	5-10℃
Heating capacity	5.0L/H	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H	2.0L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs	9kgs/10kgs
Packaging Dimension	330*340*540mm	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo			



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V/240V,50/60Hz	220V/240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs
Packaging Dimension	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo		

--	--	--



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95°C	85-95°C
Cold temperature	/	10-15°C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs
Packaging Dimension	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95°C	85-95°C
Cold temperature	/	10-15°C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs
Packaging Dimension	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95°C	85-95°C
Cold temperature	/	10-15°C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz

Mode No.



Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W



Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H



Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm





Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95 °C	85-95 °C
Cold temperature	/	10-15 °C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs
Packaging Dimension	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95 °C	85-95 °C
Cold temperature	/	10-15 °C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	4.5kgs/5.5kgs	4.5kgs/5.5kgs
Packaging Dimension	330*340*540mm	330*340*540mm
Loading Qty	476pcs/20'FT	476pcs/20'FT
	1134pcs/40'HQ	1134pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Frequency	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95 °C	85-95 °C
Cold temperature	/	10-15 °C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ

FOB Ningbo		
------------	--	--



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95 °C	85-95 °C
Cold temperature	/	10-15 °C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT 1596pcs/40'HQ	686pcs/20'FT 1596pcs/40'HQ
FOB Ningbo		

MOQ 50



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95 °C	85-95 °C
Cold temperature	/	10-15 °C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT 1596pcs/40'HQ	686pcs/20'FT 1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95 °C	85-95 °C
Cold temperature	/	10-15 °C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT 1596pcs/40'HQ	686pcs/20'FT 1596pcs/40'HQ
FOB Ningbo		

--	--	--



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	10-15℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	0.8L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	310*310*420mm	310*310*420mm
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	
Cooling Method	/	
Rated Voltage/Freque	220V240V,50/60Hz	
Heating power	550w	
Cooling power	/	
Hot temperature	85-95℃	
Cold temperature	/	
Heating capacity	5.0L/H	
Cooling capacity	/	
N.W/G.W	3.5kgs/4.5kgs	
Packaging Dimension	28*28*38	
Loading Qty	686pcs/20'FT	
	1596pcs/40'HQ	
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95℃	85-95℃
Cold temperature	/	8-12℃
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	2L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	295*355*475	295*355*475
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		

MOQ 1
container



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz



Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95°C	85-95°C
Cold temperature	/	8-12°C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	2L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	295*355*475	295*355*475
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95°C	85-95°C
Cold temperature	/	8-12°C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	2L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	295*355*475	295*355*475
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		



Function	Hot and Warm	Hot and Cold
Cooling Method	/	Electric Cooling
Rated Voltage/Freque	220V240V,50/60Hz	220V240V,50/60Hz
Heating power	550w	550w
Cooling power	/	75W
Hot temperature	85-95°C	85-95°C
Cold temperature	/	8-12°C
Heating capacity	5.0L/H	5.0L/H
Cooling capacity	/	2L/H
N.W/G.W	3.5kgs/4.5kgs	3.5kgs/4.5kgs
Packaging Dimension	295*355*475	295*355*475
Loading Qty	686pcs/20'FT	686pcs/20'FT
	1596pcs/40'HQ	1596pcs/40'HQ
FOB Ningbo		