

# Portable Air Conditioner Catalog



## Portable Air Conditioner



- Ultra compact design: 690pcs / 40HQ
- EER: Class A (EU market),DOE energy for USA market.
- Strong winds with high and low fan speeds.
- Timer 1-24hours.
- Steady cooling system enable reliable quality.
- Water full auto stop.
- High intelligent wifi control Tuya APP optional.
- With soft-touch control panel and deluxe display.

Model	GPS-01	GPS-01-1	GPS-01-2
Rated cooling capacity	1460W(5000Btu)	2050W(7000Btu)	2637W(9000Btu)
Power supply	AC220-240V/50Hz	AC220-240V/50Hz	AC220-240V/50Hz
Rated Input	557W	780W	1000W
Amps	2.5A	3.5A	4.5A
Rated EER	2.61	2.6	2.6
Refrigerant	R290/R32	R290/R32	R290/R32
Setting range	16-32°C	16-32°C	16-32°C
Air Circulation	290m <sup>3</sup> /h	290m <sup>3</sup> /h	320m <sup>3</sup> /h
Sound Power Level	≤65dB	≤65dB	≤65dB
Product dimension (HxWxD, mm)	673x303x289.5mm	673x303x289.5mm	673x303x289.5mm
Packaging dimension (HxWxD, mm)	865x355x328mm	865x355x328mm	865x355x328mm
N.W / G.W (kg)	18.5kg/22.5kg	20kg/23kg	21kg/25kg
Loading QTY 20'GP, 40'GP, 40HQ	224/462/690	224/462/690	224/462/690

## Portable Air Conditioner



- Deluxe design and control panel.
- EER: Class A (EU market), DOE energy for USA market.
- Strong winds with high and low fan speeds.
- Timer 1-24hours.
- Steady cooling system enable reliable quality.
- Water full auto stop.
- High intelligent wifi control Tuya APP optional.
- With soft-touch control panel and deluxe display.

Model	GPS-02	GPS-02-1	GPS-02-2
Rated cooling capacity	1460W(5000Btu)	2050W(7000Btu)	2600W(9000Btu)
Power supply	AC220-240V/50Hz	AC220-240V/50Hz	AC220-240V/50Hz
Rated Input	557W	780W	990W
Amps	2.5A	3.5A	4.2A
Rated EER	2.61	2.61	2.61
Refrigerant	R290/R32	R290/R32	R290/R32
Setting range	16-32°C	16-32°C	16-32°C
Air Circulation	290m <sup>3</sup> /h	290m <sup>3</sup> /h	330m <sup>3</sup> /h
Sound Power Level	≤65dB	≤65dB	≤65dB
Product dimension (HxWxD, mm)	700x300x300mm	700x300x300mm	700x300x300mm
Packaging dimension (HxWxD, mm)	884x374x346mm	884x374x346mm	884x374x346mm
N.W / G.W (kg)	18.5kg/22.5kg	20kg/23kg	21kg/25kg
Loading QTY 20'GP, 40'GP, 40HQ	192/396/592	192/396/592	192/396/592

## Portable Air Conditioner



- Deluxe design and control panel.
- EER: Class A (EU market), DOE energy for USA market.
- Strong winds with high and low fan speeds.
- Timer 1-24hours.
- Steady cooling system enable reliable quality.
- Water full auto stop.
- High intelligent wifi control Tuya APP optional.
- With soft-touch control panel and deluxe display.

Model	GPS-03	GPS-03-1	GPS-03-2
Rated cooling capacity	1460W(5000Btu)	2050W(7000Btu)	2600W(9000Btu)
Power supply	AC220-240V/50Hz	AC220-240V/50Hz	AC220-240V/50Hz
Rated Input	557W	780W	990W
Amps	2.5A	3.5A	4.2A
Rated EER	2.61	2.61	2.61
Refrigerant	R290/R32	R290/R32	R290/R32
Setting range	16-32°C	16-32°C	16-32°C
Air Circulation	290m <sup>3</sup> /h	290m <sup>3</sup> /h	330m <sup>3</sup> /h
Sound Power Level	≤65dB	≤65dB	≤65dB
Product dimension (HxWxD, mm)	700x300x300mm	700x300x300mm	700x300x300mm
Packaging dimension (HxWxD, mm)	884x374x346mm	884x374x346mm	884x374x346mm
N.W / G.W (kg)	18.5kg/22.5kg	20kg/23kg	21kg/25kg
Loading QTY 20'GP, 40'GP, 40HQ	192/396/592	192/396/592	192/396/592

## Home Dehumidifier



- Ultra mini design:1635pcs / 40HQ
- 3 colors light :Red,Green,Blue
- Intelligent 3 mode:  
Auto mode,Drying mode/Continue mode  
Sleep mode enable lower noise and without machine beep
- Intelligent touch button and top panel
- Tank full auto stop
- Auto defrost
- Built in air inlet filter to avoid Children touch.
- 2L water tank capacity, with tank cover.
- Side air outlet to avoid dust.
- Timer 1-24hours

Model	GPS-04	GPS-04-1
Dehumidifying Capacity(30°C,RH80%)	10L/ Day	12L/ Day
Power Supply	AC220V-240V/50Hz	AC220V-240V/50Hz
Power Consumption	195W	200W
Rated Current	1.2A	1.2A
Full Water Quantity	2.0L	2.0L
Noise	≤38dB	≤38dB
Air Circulation	120m <sup>3</sup> /h	120m <sup>3</sup> /h
Refrigerant	R290	R290
Working Temp	5-35°C	5-35°C
Recommend Room Size	8-15m <sup>2</sup>	8-15m <sup>2</sup>
Timer	1-24hr	1-24hr
Body Size(mm)	250x220x445mm	250x220x445mm
Package Size(mm)	305x265x500mm	305x265x500mm
N.W / G.W(Kg)	10kg/11kg	10kg/11kg
Loading Quantity(20'/40'/40'HQ)	624/1312/1635	624/1312/1635

## Home Dehumidifier



- Ultra mini design:1040pcs / 40HQ
- 3 colors light :Red,Green,Blue
- Intelligent 3 mode:
  - Auto mode,Drying mode/Continue mode
  - Sleep mode enable lower noise and without machine beep
- Intelligent touch button and top panel
- Tank full auto stop
- Auto defrost
- Built in air inlet filter to avoid Children touch.
- 4.5L water tank capacity,with tank cover.
- Timer 1-24hours

Model	GPS-05	GPS-05-1
Dehumidifying Capacity(30°C,RH80%)	16L/ Day	20L/ Day
Power Supply	220V/50Hz	220V/50Hz
Power Consumption	350W	420W
Rated Current	1.23A	2.0A
Full Water Quantity	4.5L	4.5L
Noise	≤41dB	≤41dB
Air Circulation	120m <sup>3</sup> /h	120m <sup>3</sup> /h
Refrigerant	R290	R290
Working Temp	5-35°C	5-35°C
Recommend Room Size	15-20m <sup>2</sup>	20-30m <sup>2</sup>
Timer	1-24hr	1-24hr
Body Size(mm)	321x234x519mm	321x234x519mm
Package Size(mm)	367x280x549mm	367x280x549mm
N.W / G.W(Kg)	13kg/15kg	13.5kg/15.5kg
Loading Quantity(20'/40'/40'HQ)	508/1040/1040	508/1040/1040

# Home Dehumidifier



Model	GPS-06	GPS-06-1	GPS-06-2
Dehumidifying Capacity(65°F,RH60%) DOE	22 Pints	35 Pints	50 Pints
Power Supply	AC115V/60Hz	AC115V/60Hz	AC115V/60Hz
Power Consumption	250W	365W	530W
Rated Current	2.6A	3.5A	5.0A
Full Water Quantity	4.0L	4.0L	6.5L
Noise	≤47dB	≤49dB	≤50dB
Air Circulation	210m <sup>3</sup> /h	240m <sup>3</sup> /h	340m <sup>3</sup> /h
Refrigerant	R32	R32	R32
Working Temp	5-38°C	5-38°C	5-38°C
Recommend Room Size	30-40m <sup>2</sup>	40-50m <sup>2</sup>	60-70m <sup>2</sup>
Timer	1-24hr	1-24hr	1-24hr
Body Size(mm)	380x260x500mm	392x292x635mm	392x292x635mm
Package Size(mm)	437x329x530mm	445x331x664mm	445x331x664mm
N.W / G.W(Kg)	16/18kg	17/19kg	20/22kg
Loading Quantity(20'/40'/40'HQ)	368/750/910	270/560/740	270/560/740