

Mini refrigerators Catalog



5V Household

10W ultra-low energy consumption



5V power bank

Powerable

2w milliampere power bank can provide sustainable power supply for 7-8 hours



USB car use



5V mini refrigerator

Product model	GPS-01
Rated voltage	5V
Rated power	10W
Capacity	/
material quality	ABS
Refrigeration temperature	26~27 ℃ lower than the current ambient temperature
Heating temperature	50~55℃
External dimensions of the refrigerator	193*193*216mm
Internal dimensions of the refrigerator	/
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	1.25KG
Colour	○ ● ● Whiteblackcustomizable colors



Product display >>



Product model	GPS-02
Rated voltage	5V
Rated power	10W
Capacity	4L
material quality	PP
Refrigeration temperature	18~19℃ lower than the current ambient temperature
Heating temperature	50~55℃
External dimensions of the refrigerator	197*265*280MM
Internal dimensions of the refrigerator	138*141*204MM
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	2KG
Colour	○ ● ● Whiteblackcustomizable colors



Product display >>



5V mini refrigerator

Product model	GPS-03
Rated voltage	5V
Rated power	10W
Capacity	6L
material quality	ABS
Refrigeration temperature	18-19 °C lower than the current ambient temperature
Heating temperature	50-55°C
External dimensions of the refrigerator	218*260*325mm
Internal dimensions of the refrigerator	155*150*255mm
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	2.8KG
Colour	○White ●black ●customizable colors



Product display >>



Product model	GPS-04
Rated voltage	5V
Rated power	10W
Capacity	8L
material quality	ABS
Refrigeration temperature	18-19 °C lower than the current ambient temperature
Heating temperature	50-55°C
External dimensions of the refrigerator	230*255*350mm
Internal dimensions of the refrigerator	164*174*258mm
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	3.45KG
Colour	○White ●black ●customizable colors



Product display >>



5V mini refrigerator

Product model	GPS-05
Rated voltage	5V
Rated power	10W
Capacity	10L
material quality	ABS
Refrigeration temperature	16~17 °C lower than the current ambient temperature
Heating temperature	50~55℃
External dimensions of the refrigerator	248*285*340mm
Internal dimensions of the refrigerator	180*170*276mm
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	3.6KG
Colour	○ ● ● White black customizable colors



Product display >>



Product model	GPS-06
Rated voltage	5V
Rated power	15W
Capacity	12L
material quality	ABS
Refrigeration temperature	16~17 °C lower than the current ambient temperature
Heating temperature	50~55℃
External dimensions of the refrigerator	295*320*344mm
Internal dimensions of the refrigerator	221*184*276mm
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	5KG
Colour	○ ● ● White black customizable colors



Product display >>



Product model	GPS-07
Rated voltage	5V
Rated power	15W
Capacity	20L
material quality	ABS
Refrigeration temperature	16~17 ℃ lower than the current ambient temperature
Heating temperature	50~55℃
External dimensions of the refrigerator	290*378*425mm
Internal dimensions of the refrigerator	230*230*345mm
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	6KG
Colour	○White ●black ●customizable colors



Product display >>



12V/220V Mini Refrigerator

CNC temperature control



12V/220V Mini Refrigerator

Product model	GPS-08		
Rated voltage	AC 100-125V DC 12V,60Hz	AC 100-125V DC 12V,60Hz	AC 220-240V DC 12V,50/60Hz
Rated power	AC:Cooling38W Warming30W DC:Cooling30W Warming25W	AC:50W DC:45W	AC:Cooling40W Warming25W DC:Cooling30W Warming25W
Capacity	4L		
material quality	ABS		
Refrigeration temperature	20~21 °C lower than the current ambient temperature		
Heating temperature	55~65℃		
External dimensions of the refrigerator	205*255*275mm		
Internal dimensions of the refrigerator	136*140*203mm		
Power plug	American regulations	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	ETL、FCC	PSE	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	2.5KG		
Colour	○White ●black ●customizable colors		



Product display >>



Product model	GPS-09		GPS-10
Rated voltage	AC 100-125V DC 12V,60Hz	AC 220-240V DC 12V,50/60Hz	AC 100-125V DC 12V,60Hz
Rated power	AC:Cooling38W Warming30W DC:Cooling30W Warming25W	AC:Cooling40W Warming25W DC:Cooling30W Warming25W	AC:50W DC:45W
Capacity	4L		
material quality	PP		
Refrigeration temperature	18~19 °C lower than the current ambient temperature		
Heating temperature	55~65℃		
External dimensions of the refrigerator	197*265*280MM		
Internal dimensions of the refrigerator	138*141*204MM		
Power plug	American regulations	Chinese regulations, British regulations, European regulations, Korean regulations, Australian regulations	Japanese regulations
Authentication	ETL、FCC	CCC、CE、UK、CB、KC、SAA	PSE
Gross weight of refrigerator	2.2KG		
Colour	○White ●black ●customizable colors		



Product display >>



12V/220V Mini Refrigerator

Product model	GPS-11		
Rated voltage	AC 100–125V DC 12V,60Hz	AC 100–125V DC 12V,60Hz	AC 220–240V DC 12V,50/60Hz
Rated power	AC:Cooling50W Warming45W DC:Cooling45W Warming40W	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	6L		
material quality	ABS		
Refrigeration temperature	19~20 ℃ lower than the current ambient temperature		
Heating temperature	55~65℃		
External dimensions of the refrigerator	218*260*325mm		
Internal dimensions of the refrigerator	155*150*255mm		
Power plug	American regulations	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	ETL、FCC	PSE	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	3KG		
Colour	○ White ● black 🌈 customizable colors		



Product display >>



Product model	GPS-12		GPS-13
Rated voltage	AC 100–125V DC 12V,60Hz	AC 220–240V DC 12V,50/60Hz	AC 100–125V DC 12V,60Hz
Rated power	AC:Cooling50W Warming45W DC:Cooling45W Warming40W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W	AC:60W DC:50W
Capacity	6L		
material quality	ABS		
Refrigeration temperature	19~20 ℃ lower than the current ambient temperature		
Heating temperature	55~65℃		
External dimensions of the refrigerator	218*260*325mm		
Internal dimensions of the refrigerator	155*150*255mm		
Power plug	American regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations	Japanese regulations
Authentication	ETL、FCC	CCC、CE、UK、CB、KC、SAA	PSE
Gross weight of refrigerator	3KG		
Colour	○ White ● black 🌈 customizable colors		



Product display >>



12V/220V Mini Refrigerator

Product model	GPS-14	GPS-15
Rated voltage	AC 100–125V,60Hz	AC 220–240V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	6L	
material quality	ABS	
Refrigeration temperature	19-20 °C lower than the current ambient temperature	
Heating temperature	/	
External dimensions of the refrigerator	218*260*325mm	
Internal dimensions of the refrigerator	155*150*255mm	
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	3.5KG	
Colour	White ● black ● customizable colors	



Product display >>



Product model	GPS-16	GPS-17
Rated voltage	AC 100–125V DC 12V,60Hz	AC 220–240V DC 12V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	8L	
material quality	ABS	
Refrigeration temperature	18-19 °C lower than the current ambient temperature	
Heating temperature	55-65℃	
External dimensions of the refrigerator	230*255*350mm	
Internal dimensions of the refrigerator	164*174*258mm	
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	3.65KG	
Colour	White ● black ● customizable colors	



Product display >>



12V/220V Mini Refrigerator

Product model	GPS-18		
Rated voltage	AC 100-125V DC 12V,60Hz	AC 100-125V DC 12V,60Hz	AC 220-240V DC 12V,50/60Hz
Rated power	AC:Cooling50W Warming45W DC:Cooling45W Warming40W	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	9L		
material quality	ABS		
Refrigeration temperature	17~18 °C lower than the current ambient temperature		
Heating temperature	55~65°C		
External dimensions of the refrigerator	373*191*284mm		
Internal dimensions of the refrigerator	255*150*237mm		
Power plug	American regulations	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	ETL、FCC	PSE	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	3.5KG		
Colour	○White ●black ●customizable colors		



Product display >>



Product model	GPS-19	GPS-20
Rated voltage	AC 220-240V DC 12V,50/60Hz	AC 100-125V DC 12V,60Hz
Rated power	AC:Cooling55W Warming50W DC:Cooling45W Warming40W	AC:60W DC:50W
Capacity	9L	
material quality	ABS	
Refrigeration temperature	19~20 °C lower than the current ambient temperature	
Heating temperature	55~65°C	
External dimensions of the refrigerator	445*235*280mm	
Internal dimensions of the refrigerator	280*157*180mm	
Power plug	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations	Japanese regulations
Authentication	CCC、CE、UK、CB、KC、SAA	PSE
Gross weight of refrigerator	4.8KG	
Colour	○White ●black ●customizable colors	



Product display >>



12V/220V Mini Refrigerator

Product model	GPS-21
Rated voltage	AC 220–240V,DC 12V,50/60Hz
Rated power	AC:Cooling75W Warming70W DC:Cooling60W Warming65W
Capacity	9L
material quality	ABS
Refrigeration temperature	26~27 °C lower than the current ambient temperature
Heating temperature	65°C
External dimensions of the refrigerator	445*235*280mm
Internal dimensions of the refrigerator	280*157*180mm
Power plug	Chinese regulations, British regulations, European regulations, Korean regulations, Australian regulations
Authentication	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	5.2KG
Colour	○ White ● black ● customizable colors



Product display >>



Product model	GPS-22		
Rated voltage	AC 100–125V DC 12V,60Hz	AC 100–125V DC 12V,60Hz	AC 220–240V DC 12V,50/60Hz
Rated power	AC:Cooling50W Warming45W DC:Cooling45W Warming40W	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	10L		
material quality	ABS		
Refrigeration temperature	19~20 °C lower than the current ambient temperature		
Heating temperature	55~65°C		
External dimensions of the refrigerator	248*285*340mm		
Internal dimensions of the refrigerator	180*170*276mm		
Power plug	American regulations	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	ETL、FCC	PSE	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	3.8KG		
Colour	○ White ● black ● customizable colors		



Product display >>



12V/220V Mini Refrigerator

Product model	GPS-23	GPS-24
Rated voltage	AC 100–125V DC 12V,60Hz	AC 220–240V DC 12V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	10L	
material quality	ABS	
Refrigeration temperature	19~20 ℃ lower than the current ambient temperature	
Heating temperature	55~65℃	
External dimensions of the refrigerator	248*285*340mm	
Internal dimensions of the refrigerator	180*170*276mm	
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	4.4KG	
Colour	○White ●black 🌈customizable colors	



Product display >>



Product model	GPS-25
Rated voltage	AC 220–240V,DC 12V,50/60Hz
Rated power	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	10L
material quality	ABS
Refrigeration temperature	19~20 ℃ lower than the current ambient temperature
Heating temperature	65℃
External dimensions of the refrigerator	248*285*340mm
Internal dimensions of the refrigerator	180*170*276mm
Power plug	Chinese regulations, British regulations, European regulations, Korean regulations, Australian regulations
Authentication	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	4.3KG
Colour	○White ●black 🌈customizable colors



Product display >>



12V/220V Mini Refrigerator

Product model	GPS-26
Rated voltage	AC 220–240V,DC 12V,50/60Hz
Rated power	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	10L
material quality	ABS
Refrigeration temperature	19~20 ℃ lower than the current ambient temperature
Heating temperature	/
External dimensions of the refrigerator	248*285*340mm
Internal dimensions of the refrigerator	180*170*276mm
Power plug	Chinese regulations, British regulations, European regulations, Korean regulations, Australian regulations
Authentication	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	4.35KG
Colour	○White ●black ●customizable colors



Product display >>



Product model	GPS-27		GPS-28
Rated voltage	AC 100–125V DC 12V,60Hz	AC 220–240V DC 12V,50/60Hz	AC 220–240V DC 12V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W	AC:Cooling75W Warming70W DC:Cooling60W Warming65W
Capacity	12L		
material quality	ABS		
Refrigeration temperature	18~19 ℃ lower than the current ambient temperature		25~26℃ lower than the current ambient temperature
Heating temperature	55~65℃		65℃
External dimensions of the refrigerator	295*320*344mm		
Internal dimensions of the refrigerator	221*184*276mm		
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA	CCC、CE、UK、CB、KC、SAA、ERP
Gross weight of refrigerator	5KG		5.8KG
Colour	○White ●black ●customizable colors		



Product display >>



12V/220V Mini Refrigerator

Product model	GPS-29
Rated voltage	AC 220~240V,DC 12V,50/60Hz
Rated power	AC:Cooling75W Warming70W DC:Cooling60W Warming65W
Capacity	12L
material quality	ABS
Refrigeration temperature	25~26 ℃ lower than the current ambient temperature
Heating temperature	65℃
External dimensions of the refrigerator	450*327*262mm
Internal dimensions of the refrigerator	280*225*185mm
Power plug	Chinese regulations, British regulations, European regulations, Korean regulations, Australian regulations
Authentication	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	7.4KG
Colour	○White ●black ●customizable colors



Product display >>



Product model	GPS-30	
Rated voltage	AC 100~125V DC 12V,60Hz	AC 220~240V DC 12V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	15L	
material quality	ABS	
Refrigeration temperature	19~20 ℃ lower than the current ambient temperature	
Heating temperature	/	
External dimensions of the refrigerator	280*286*440mm	
Internal dimensions of the refrigerator	226*140*380mm	
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	5KG	
Colour	○White ●black ●customizable colors	



Product display >>



12V/220V Mini Refrigerator

Product model	GPS-31	GPS-32
Rated voltage	AC 100–125V DC 12V,60Hz	AC 220–240V DC 12V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W
Capacity	15L	
material quality	ABS	
Refrigeration temperature	19~20 ℃ lower than the current ambient temperature	
Heating temperature	/	
External dimensions of the refrigerator	280*286*440mm	
Internal dimensions of the refrigerator	226*140*380mm	
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA
Gross weight of refrigerator	5KG	
Colour	○White ●black ●customizable colors	



Product display >>



Product model	GPS-33		GPS-34
Rated voltage	AC 100–125V DC 12V,60Hz	AC 220–240V DC 12V,50/60Hz	AC 220–240V DC 12V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W	AC:Cooling75W Warming70W DC:Cooling60W Warming65W
Capacity	20L		
material quality	ABS		
Refrigeration temperature	18~19 ℃ lower than the current ambient temperature		25~26℃ lower than the current ambient temperature
Heating temperature	55~65℃		65℃
External dimensions of the refrigerator	290*378*425mm		
Internal dimensions of the refrigerator	230*230*345mm		
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA、ERP	CCC、CE、UK、CB、KC、SAA、ERP
Gross weight of refrigerator	6.2KG		6.7KG
Colour	○White ●black ●customizable colors		



Product display >>



Dual core refrigeration system

Rapid cooling with an ambient temperature of
25 °C up to 0 °C

Dual core system



Dual core system

Intelligent Mute

Professional zoning

12V/220V Mini Refrigerator

Product model	GPS-35		GPS-36
Rated voltage	AC 100~125V DC 12V,60Hz	AC 220~240V DC 12V,50/60Hz	AC 220~240V DC 12V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W	AC:Cooling75W Warming70W DC:Cooling60W Warming65W
Capacity	20L		
material quality	ABS		
Refrigeration temperature	18~19 ℃ lower than the current ambient temperature		25~26℃ lower than the current ambient temperature
Heating temperature	55~65℃		65℃
External dimensions of the refrigerator	290*378*425mm		
Internal dimensions of the refrigerator	230*230*345mm		
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA、ERP	CCC、CE、UK、CB、KC、SAA、ERP
Gross weight of refrigerator	6.8KG		7.5KG
Colour	○White ●black 🌈customizable colors		



Product display >>



Product model	GPS-37		GPS-38
Rated voltage	AC 100~125V DC 12V,60Hz	AC 220~240V DC 12V,50/60Hz	AC 220~240V DC 12V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W	AC:Cooling75W Warming35W DC:Cooling60W Warming40W
Capacity	22L		
material quality	ABS		
Refrigeration temperature	18~19 ℃ lower than the current ambient temperature		25~26℃ lower than the current ambient temperature
Heating temperature	55~65℃		65℃
External dimensions of the refrigerator	310*340*510mm		
Internal dimensions of the refrigerator	235*205*425mm		
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA、ERP	CCC、CE、UK、CB、KC、SAA、ERP
Gross weight of refrigerator	6.6KG		7.3KG
Colour	○White ●black 🌈customizable colors		



Product display >>



12V/220V Mini Refrigerator

Product model	GPS-39		GPS-40
Rated voltage	AC 100–125V DC 12V,60Hz	AC 220–240V DC 12V,50/60Hz	AC 220–240V DC 12V,50/60Hz
Rated power	AC:60W DC:50W	AC:Cooling55W Warming50W DC:Cooling45W Warming40W	AC:Cooling75W Warming35W DC:Cooling60W Warming40W
Capacity	22L		
material quality	ABS		
Refrigeration temperature	18~19 ℃ lower than the current ambient temperature		25~26℃ lower than the current ambient temperature
Heating temperature	55~65℃		65℃
External dimensions of the refrigerator	310*340*510mm		
Internal dimensions of the refrigerator	235*205*425mm		
Power plug	Japanese regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations	Chinese regulations, British regulations, European regulations,Korean regulations, Australian regulations
Authentication	PSE	CCC、CE、UK、CB、KC、SAA、ERP	CCC、CE、UK、CB、KC、SAA、ERP
Gross weight of refrigerator	7.7KG		8.2KG
Colour	○White ●black 🌈customizable colors		



Product display >>



K20 Car mounted compressor refrigerator

CNC temperature control:
20~(-20) °C



Car mounted compressor refrigerator

Product model	GPS-41
Rated voltage	AC 100~240V,DC 12V/24V,50/60Hz
Rated power	AC 45W ,DC 40W
Capacity	15L
material quality	ABS+PE
Refrigeration temperature	20~(-20) ℃
External dimensions of the refrigerator	587*375*296mm
Internal dimensions of the refrigerator	300*250*196mm
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	12.6KG
Colour	● black ● customizable colors



Product display >>



Product model	GPS-42
Rated voltage	AC 100~240V,DC 12V/24V,50/60Hz
Rated power	AC 45W ,DC 40W
Capacity	20L
material quality	ABS+PE
Refrigeration temperature	20~(-20) ℃
External dimensions of the refrigerator	560*350*354mm
Internal dimensions of the refrigerator	260*230*248mm (frozen area) 135*230*70mm (micro frozen area)
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	12.6KG
Colour	● black ● customizable colors



Product display >>



Car mounted compressor refrigerator

Product model	GPS-43
Rated voltage	AC 100~240V,DC 12V/24V,50/60Hz
Rated power	AC 45W ,DC 40W
Capacity	30L
material quality	ABS+PE
Refrigeration temperature	20-(-20) ℃
External dimensions of the refrigerator	590*350*446mm
Internal dimensions of the refrigerator	260*243*340mm (frozen area) 170*243*160mm(micro frozen area)
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	14KG
Colour	● black ● customizable colors



Product display >>



Product model	GPS-44
Rated voltage	AC 100~240V,DC 12V/24V,50/60Hz
Rated power	AC 48W ,DC 43W
Capacity	15L
material quality	PP
Refrigeration temperature	10-(-20) ℃
External dimensions of the refrigerator	550*310*280mm
Internal dimensions of the refrigerator	330*230*170mm
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	11KG
Colour	● black ● customizable colors



Product display >>



Car mounted compressor refrigerator

Product model	GPS-45
Rated voltage	AC 100~240V,DC 12V/24V,50/60Hz
Rated power	AC 48W ,DC 43W
Capacity	20L
material quality	PP
Refrigeration temperature	10~(-20) ℃
External dimensions of the refrigerator	550*310*370mm
Internal dimensions of the refrigerator	330*230*250mm
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、ETL、FCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	12KG
Colour	● black ● customizable colors



Product display >>



**Lightweight
Portable**

Easy to take away



Mini refrigerator

Product model	GPS-46
Rated voltage	AC220–240V,50/60Hz
Rated power	55
Capacity	30L
material quality	ABS+PE
Refrigeration temperature	10~(-20) °C
External dimensions of the refrigerator	373*378*658mm
Internal dimensions of the refrigerator	Freezing room(8L)+Refrigeration room(22L)
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	15KG
Colour	black customizable colors



Product display >>



Product model	GPS-47
Rated voltage	AC220–240V,50/60Hz
Rated power	55
Capacity	32L
material quality	ABS+PE
Refrigeration temperature	10~(-20) °C
External dimensions of the refrigerator	380*360*630mm
Internal dimensions of the refrigerator	Freezing(8L)+Refrigeration room(24L)
Power plug	Chinese regulations, American regulations, Japanese regulations, European regulations, Korean regulations, British regulations, Australian regulations, etc
Authentication	CCC、PSE、UK、SAA、KC、CE, etc.
Gross weight of refrigerator	14.2KG
Colour	black customizable colors



Product display >>



G650 Car heated cup

CNC temperature control: 25~90°C



Car mounted heating cup

Product model	GPS-48
Rated voltage	DC 12V
Rated power	70W
Capacity	350ML
material quality	tritan+PC
Heating temperature	25~90℃
External dimensions of the refrigerator	height(210mm),width(75mm)
Authentication	FDA、CE、ROHS
Gross weight of refrigerator	0.7KG
Colour	● black ● customizable colors



Product display >>



Product model	GPS-49
Rated voltage	DC 12V
Rated power	70W
Capacity	350ML
material quality	tritan+PC
Heating temperature	25~90℃
External dimensions of the refrigerator	height(218mm),width(85mm)
Authentication	FDA、CE、ROHS
Gross weight of refrigerator	0.65KG
Colour	● black ● customizable colors



Product display >>



Car mounted heating cup

Product model	GPS-50
Rated voltage	DC 12V
Rated power	70W
Capacity	350ML
material quality	tritan+PC
Heating temperature	25~90℃
External dimensions of the refrigerator	height(227mm),width(83mm)
Authentication	FDA、CE、ROHS
Gross weight of refrigerator	0.7KG
Colour	● black ● customizable colors



Product display >>



Product model	GPS-51
Rated voltage	DC 12V
Rated power	70W
Capacity	420ML
material quality	PP+PC
Heating temperature	25~90℃
External dimensions of the refrigerator	height(290mm),width(90mm)
Authentication	FDA、CE、ROHS
Gross weight of refrigerator	0.85KG
Colour	● black ● customizable colors



Product display >>

