

**Vous l'Imaginez,
Nous le Fabriquons**

Nous Connectons Les Meilleurs Fabricants du monde à Votre Entreprise

Les Nouveautés LED

Juillet 2025



YOUR SMART **G**LOBAL **P**ROCUREMENT & **S**OURCING PARTNER


Avec plus de 27 ans d'expérience, GPS Monaco Group est votre Allié de Confiance en matière de Sourcing et d'Approvisionnement International.

NOS AVANTAGES



Excellence à Votre Service

Nous nous efforçons constamment de dépasser les attentes de nos clients en leur offrant des solutions et des services de premier ordre.



Approche Sur Mesure

Notre approche centrée sur le client vous fournit des solutions sur mesure pour vos besoins uniques.



Présence Internationale

Depuis nos bureaux à Monaco, France, Suisse, Asie et Arabie Saoudite, nous sécurisons vos achats de l'usine à vos entrepôts.

Plus de
60
Millions
de Produits Importés.

+1700
Usines Auditées.



- Product size : 45*48*52cm
- Pole : 5°/10°
- Color : Matte black / Matte white / Grey / Green
- Material : Plywood
- Power : 24W
- Remote control : 3CCT + 6 speed
- Motor : DC35W, Fine copper, D153MM
- CE / CB



- Power : 12W / 24W / 36W / 42W
- Lumens : 1080lm / 2160lm / 3240lm / 3780lm
- Angle : 120°
- IP65
- Size : ø200xH40mm / ø280xH40mm / ø380xH40 / ø480xH40
- 3 CCT optional DIP switch : 3000K-4000K-6000K



Longer lifetime

Strict selection of high quality drive (Lifud)



Quick Connector

42mm (7W)

lamp height suit for different height ceiling.



Front



Back

UGR < 19

Avoid glare and visual fatigue effectively.

HIGH EFFICIENCY HEAT DISSIPATION

Modified plastic mix aluminum powder lamp housing with make sure longer lifetime.



120° Beam Angle ANTI-GLARE



FLICKER FREE

Stable current output
no stroboscopic.

- Voltage : 170-260V
- IP20 / UGR <19 / Ra>80
- Color temp : 3000K / 4000K / 6000K
- Power : 7W / 12W / 18W / 24W / 30W
- Lumens : 600lm / 1150lm / 1650lm / 2250lm / 2850lm
- Lumens version quick connector : 1000lm / 1700lm / 2650lm / 3500lm / 4350lm
- Beam angle : 120°
- Quick connector option
- CE / CB / RoHS - Flicker free



The matching hook and 0.5M Type C cable, 18650 3.7v 1500mAH lithium battery.
The lamp body has a touch switch. The accompanying remote control is available from 3000K to 6500K, with adjustable color temperature and brightness
The 230V high voltage can be used as a normal bulb. When the power is off, it can be battery-powered for lighting

- Voltage : 185-265V
- Color temperature : 3000K/4000K/6500K
- Material : PA + PC
- Ra $\geq$ 0.8
- PF : $\geq$ 0.5
- Lumens : 700lm
- Product size : $\varnothing$ 65*136mm
- E27 / IP20
- Beam angle : 180°
- Discharge time : 5 to 24 hours



- Battery type Li-on
- Charging time : 6-8h
- Operation time : 8-10h
- Light control / IP54
- Color temperature : 2700K
- Lumens : 30lm
- CE UKCA / RoHS
- Battery capacity : 3.7V/2200mAh - 3.7V/1500mAh
- Solar panel power : 5V/1.5W (Monocrystalline) - 5V/1.3W (Monocrystalline)
- Product size : 640*265*73mm - 200*154*182mm



Patrick Bogaerts
Fondateur, CEO

Contact

Téléphone : +33 6 07 93 79 98

Email : Patrick@GPSMonacoGroup.com

Site Web : <https://GPSMonacoGroup.com>